TORUS

TRS-260 Mono



IP67 (E



 $YYZ\ Torus\ LED\ in ground\ light for\ outdoor\ lighting\ applications.\ Transparent\ and\ Frosted\ covers/\ diffusers\ with$ buried mounting sleeves and accessories help to form uniform lighting. These inground LED lighting fixtures will create a beautiful ambiance and enhance the environment. The fixtures are versatile which can add a visual impact and also plays a critical role in safety apart from lighting.

FEATURES

MATERIAL STAINLESS STEEL WORKING VOLTAGE 24V DC, 100-240V AC

RATED POWER 20/30W 18°/30°/40°/60° **BEAM ANGLE** LAMP LIFE 50,000 HRS MOUNTING FLOOR RECESSED **DIMENSIONS** Ø260x224mm **OPERATION TEMP** -20° C - +50° C **BODY COLOR**

STAINLESS STEEL









ELECTRICAL DATA


POWER CONSUMPTION 20/30W


SUPPLY VOLTAGE 24V DC, 100-240V AC

2700K, 3000K, 4000K, 5000K, 6000K COLORS

On/Off CONTROL 80+ CRI 42-45lm /W LUMEN

DIMENSION







Bullseyes Louver

ORDERING LOGIC

PRODUCT	WATTAC	E COL	OR TEMPERATURE	VOLTAGE	BEAM ANGLE		FINISH		CUSTOM			
TRS 260	20 - 20	W (CT2	7) 2700K	24 - 24V DC	20	-	20°	SS -	Stainless Steel	XX	- :	XX
	30 - 30	w (CT3	0) 3000K	AC -240V AC	30	-	30°					
		(CT4	0) 4000K		40	-	40°					
		(CT5	0) 5000K		35x53	35	°x53°					
		(CT6	0) 6000K		40x70	- 40	°x70°					
					50x95 - 50°x95°							

Sample: TRS 260 - 20 - CT27 - 24 - 20 - SS - BL - XX