# LINEAR RECESSED OUTDOOR





IP67 WATER PROOF

 $\epsilon$ 

YYZ LRO series is the linear recessed fixture build in constant current drive and 485 control module inside rendering it a reliable solution for interactive function between person and light. This IP67 rated fixture has carefully designed embedded parts and is easy to install. It has waterproof design and matching degassing valve make it suitable for application in areas like public square, park, stage, garden etc.

#### **FEATURES**

LED QUANTITY 36Led/mtr

FINISH 6063-T5 Aluminum

WORKING VOLTAGE 24 V dc RATED POWER 36W/mtr

BEAM ANGLE 8°x8°, 15°x15°, 30°x30°, 45°x45°, 60°x60°, 9°x50°, 10°x60°

DELIVERED OUTPUT 118lm @ 4000K

AVAILABLE LENGTH 500mm, 1000mm

MOUNTING Recessed

OPTIC Tempered glass

DIMENSIONS 500/1000(L) v 52/0

 DIMENSIONS
 500/1000(L) x 52(W)

 OPERATION TEMP
 -5° C - +50° C

 STORAGE TEMP
 -20° C - +60° C

 WEIGHT
 3.70kg/mtr

 LAMP LIFE
 50000 hrs

BODY COLOR Black, Grey, Custom CONTROL On/Off, Dali, 1-10V







### **ELECTRICAL DATA**


POWER CONSUMPTION 36W/ mtr SUPPLY VOLTAGE 24 DC Volts

COLORS 2700K, 3000K, 4000K

CRI 80+ LEDS / 3.3FT 36 LEDS

LUMEN 118lm/W @ 4000K

### **DIMENSION**



## **ORDERING LOGIC**

PRODUCT	OPTIC		COLOR TEMPARTURE		VOLTAGE	FIXTURE LENGTH		BODY COLOR			CUSTOM
LRO36	8	- 8° x 8°	(CT27)	2700K	24 - 24VDC	500 -	500mm (18 LEDS)	BK	-	BLACK	XX
	15	- 5° x 15°	(CT30)	3000K		1000 -	1000mm (36LEDS)	GR	-	GREY	
	30	- 30° x 30°	(CT40)	4000K		XX -	CUSTOM	XX	-	CUSTOM	
	45	- 45° x 45°	(CTXX)	CUSTOM							
	60	- 60° x 60°									
	9x50	- 9° x 50°									
	10x60	$^{-}~10^{\circ}x60^{\circ}$									
	XX	- CUSTOM				Γ	Sample: LRO36 - 8 - CT 27 - 24			500 - BK - X	(