

# DIMPLE WWRT

## DPL WWRT



YYZ Dimple is a linear sleek recessed slot light with a trim and interior curve feature. The luminaire can be installed both vertically and horizontally to form continuous or individual rows. It is made from 100% recyclable, extruded architectural grade T6061 aluminum and is with several LED lamping options including multiple outputs and CCTs, tunable white and colour changing RGB+White. A Low UGR option is available with a prismatic lens is also available.

### FEATURES


HOUSING	100% Recyclable, extruded architectural grade t6061 aluminium
FINISH	Aluminium, Black, White, Ral, Bronze powdercoat
RATED POWER	12/13.4/25W/mtr
BEAM ANGLE	120°
MOUNTING	Recessed
OPTIC	Opal diffuser
DIMENSIONS	40(57 with trim) mm x 58 mm
OPERATION TEMP	-20° C - +40° C
LAMP LIFE	50,000 hrs
AVAILABLE LENGTH	600, 1200, 1800, 2400, 3000, 3400, 4500, 5000mm
CONTROL	0-10V, 1-10V, Dali, Dmx, Non dimmable, Phase dim



### ELECTRICAL DATA

POWER CONSUMPTION	12/13.4/25W/mtr
SUPPLY VOLTAGE	220-240 Vac
COLORS	2700k, 3000K, 3500k, 4000K, 5000k, 6500K
CRI	80+

### DIMENSION



### ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	DRIVER	FINISH	LUMEN OUTPUT	OPTIONS
DIMPLE WWRT - DPLWWRT	12 - 12W/Mtr	(CT27) 2700K	0-10V	AL - Aluminium natural	M - Minium 707lm/m	EM - 3 Hour Emergency Kit-Remote
	13.4 - 13.4W/Mtr	(CT30) 3000K	1-10V	BK - Black powder coat	L - Low 1010lm/m	PIR-A - PIR Absence Detector - remote
	25 - 25W/Mtr	(CT35) 3500K	DALI	WH - White powder coat	ME - Medium 1970lm/m	PIR-P - PIR Presence Detector - remote
		(CT40) 4000K	NON DIM	RAL - RAL powder coat	RGBW - RGBW 238lm/m(white onlt)	(XX) - Custom
		(CT50) 5000K	DMX	BR - Bronze powder coat		
		(CT65) 6500K	PHASE DIM			
		(CTXX) CUSTOM				

Sample: DPLWWRT - 12 - CT 27 - 0-10V - AL - M - EM