### INDOOR LFX COB SERIES

LFX-I-12.00-CTXX-COB-Z3-360-12-CV-10-H-1-HT-RMTLWL05



## STAPE NON-WATER PROOF CE 12.0W

YYZ LFX COB IP20 series features excellent homogenous light, without visible light points. The COB strip is a high-density led lighting strip made by COB encapsulation, which can reduce the thermal resistance of the high-density strip circuit system, greatly improves the life of the LED, and the light flux density is high, the glare is small, and the light is uniform. These series is perfect for indirect lighting and hence used in offices, residential interiors, furniture, or places which require large luminous surface.

### FEATURES

| LIGHT SOURCE       |
|--------------------|
| LED QUANTITY       |
| FINISH             |
| WORKING VOLTAGE    |
| RATED POWER        |
| RADIANCE ANGLE     |
| LAMP LIFE          |
| MOUNTING           |
| CONNECTION         |
| CUTTING INCREMENTS |
| DIMENSIONS         |
| MAX DAISY RUN      |

COB 360 Leds / mtr White PCB 12 Volts 12W / mtr 180° 50000 hrs 3M Tape on the back Hardwired tails Every 25mm 2500 x 10mm 2.5 mtr





IP 20(Indoor)

#### ELECTRICAL DATA

| POWER CONSUMPTION | 12.0W                             |
|-------------------|-----------------------------------|
| SUPPLY VOLTAGE    | 12 Vdc                            |
| SUPPLY CURRENT    | 240V ac                           |
| COLORS            | 2700K, 3000K, 4000K, 5000K, 6000K |
| CRI               | >90                               |
| LUMEN             | 820-1050lm                        |
|                   |                                   |

#### **ORDERING LOGIC**

| PRODUCT<br>SERIES | ТҮРЕ                 | POWER         | COLOR<br>TEMPERATURE       |   | LED TYPE | BIN | NO. OF LED            | VOLTAGE | CIRCUIT                | РСВ              | CRI                            | NO OF LED<br>ROWS | CONNECTION                                   | I                  |
|-------------------|----------------------|---------------|----------------------------|---|----------|-----|-----------------------|---------|------------------------|------------------|--------------------------------|-------------------|--|--------------------|
| LFX               | I - INDOOR<br>(IP20) | 12.00 - 12.0W | (CT30)<br>(CT40)<br>(CT50) | 2700K<br>3000K<br>4000K<br>5000K<br>6000K | СОВ      | Z3  | 360 - 360<br>LEDs/mtr | 12-12V  | CV-Constant<br>voltage | 10 - 10mm        | H - HIGH (90)                  | 1                 | HT - Hardwired Tail<br>IC - Indoor Connector |                    |
|                   |                      |               | (0100)                     | OUUK                                      |          |     |                       |         | MODEL                  | COLOR<br>CONTROL | LIGHT<br>EMITTING<br>DIRECTION | LED<br>POWER      | PCB<br>COLOR                                 | LENGTH<br>PER REEL |
|                   |                      |               |                            |   |          |     |                       |         | R - Regular            | M - Mono         | Т - Тор                        | L - Low           | W - White                                    | L05 - 5mtr         |

Sample: LFX - I - 12.00 - CT 27 - COB - Z3 - 360 - 12 - CV - 10 - H - 1 - HT - RMTLWL05

# INDOOR LFX COB SERIES

LFX-I-12.00-CTXX-COB-Z3-360-12-CV-10-H-1-HT-RMTLWL05



#### DIMENSIONS






#### **BINNING DIAGRAM**

**BIN Details** 





#### **ACCESSORIES**

Surface mounted

Hanging installation









Corner installation

Recessed installation





Built-in

installation

LFX COB Series