OUTDOOR LFX COB SERIES







3M TAPE

IP65 WATER PROOF



cUlus ← 12.0W

YYZ LFX COB IP65 series features excellent homogenous light, without visible light points. The COB strip is a high-density led lighting strip made by COB encapsulation, which can reduce the thermal resistance of the high-density strip circuit system, greatly improves the life of the LED, and the light flux density is high, the glare is small, and the light is uniform. These series is perfect for indirect lighting and hence used in offices, residential interiors, furniture, or places which require large luminous surface.



FEATURES

LIGHT SOURCE СОВ

LED QUANTITY 360 Leds / mtr **FINISH** White PCB WORKING VOLTAGE 12 Volts RATED POWER 12W / mtr RADIANCE ANGLE 180° LAMP LIFE 50000 hrs

MOUNTING 3M Tape on the back CONNECTION Hardwired tails **CUTTING INCREMENTS** Every 25mm **DIMENSIONS** 2500 x 10mm MAX DAISY RUN 2.5 mtr













ELECTRICAL DATA

POWER CONSUMPTION 12.0W SUPPLY VOLTAGE 12 Vdc SUPPLY CURRENT 240V ac

2700K, 3000K, 4000K, 5000K, 6000K **COLORS**

CRI

LUMEN 820-1050lm

ORDERING LOGIC

PRODUCT SERIES	ТҮРЕ	POWER	COLOR TEMPERATUR	LED TYPE	BIN	NO. OF LED	VOLTAGE	CIRCUIT	РСВ	CRI	NO OF LED ROWS	CONNECTION	
LFX	O - Outdoor (IP65)	12.00 - 12.0W	(CT27) 27001 (CT30) 30001 (CT40) 40001 (CT50) 50001		Z3	360 - 360 LEDs/mtr	12-12V	CV-Constant voltage	10 - 10mm	H - HIGH (90)	1	HT - Hardwire OC - Outdoor	
			(CT60) 6000I					MODEL	COLOR CONTROL	LIGHT EMITTING DIRECTION	LED POWER	PCB COLOR	LENGTH PER REEL
								R - Regular	M - Mono	T - Top	L - Low	W - White	L05 - 5mtr

Sample: LFX - O - 12.00 - CT 27 - COB - Z3 - 360 - 12 - CV - 10 - H -1 - HT - RMTLWL05






DIMENSIONS



BINNING DIAGRAM

BIN Details



ACCESSORIES

Surface mounted









2020

Hanging installation

2020B

1616

Corner installation



Recessed installation





