# **OUTDOOR LFX COB SERIES**















YYZ LFX COB IP67 series features excellent homogenous light, without visible light points. The COB strip is a high-density led lighting strip made by COB encapsulation, which can reduce the thermal resistance of the high-density strip circuit system, greatly improves the life of the LED, and the light flux density is high, the glare is small, and the light is uniform. These series is perfect for indirect lighting and hence used in offices, residential interiors, furniture, or places which require large luminous surface.



### **FEATURES**

LIGHT SOURCE СОВ

LED QUANTITY 320 Leds / mtr **FINISH** White PCB WORKING VOLTAGE 24 Volts RATED POWER 8W/mtr RADIANCE ANGLE 180° LAMP LIFE 50000 hrs

MOUNTING 3M Tape on the back CONNECTION Hardwired tails **CUTTING INCREMENTS** Every 50mm **DIMENSIONS** 5000 x 8mm MAX DAISY RUN 5 mtr



CREE







IP 67(Diamond)



### **ELECTRICAL DATA**

POWER CONSUMPTION 8.0W 24 Vdc SUPPLY VOLTAGE SUPPLY CURRENT 240V ac

2700K, 3000K, 4000K, 5000K, 6000K **COLORS** 


CRI

LUMEN 800-1000lm

#### **ORDERING LOGIC**

				NO. OF LED	VOLTAGE	CIRCUIT	РСВ	CRI	NO OF LED ROWS	CONNECTION	
LFX O - Outdoo (IP67)	08.00 - 8.0W	(CT27) 2700H (CT30) 3000H (CT40) 4000H (CT50) 5000H (CT60) 6000H	Z3	320 - 320 LEDs/mtr	24-24V	CV-Constant voltage	08 - 8mm	H - HIGH (90)	1	HT - Hardwire OC - Outdoor	
		(0100) 6000				MODEL	COLOR CONTROL	LIGHT EMITTING DIRECTION	LED POWER	PCB COLOR	LENGTH PER REEL
						R - Regular	M - Mono	Т - Тор	L - Low	W - White	L05 - 5mtr

Sample: LFX - O - 08.00 - CT 27 - COB - Z3 - 320 - 24 - CV - 08 - H -1 - HT - RMTLWL05






#### **DIMENSIONS**



#### **BINNING DIAGRAM**

#### **BIN Details**



## **ACCESSORIES**

Surface mounted









Hanging installation







Corner installation

Recessed installation







Page 2 of 2