CHAMAELEO RESIDENTIAL SERIES







IP20,44 (€

 ${\it YYZ\,Chamae leo\,Residential\,series}, perfect spot \, lighting\, or\, accentuation\, with\, an\, almost\, invisible\, light \, aperture$ is ideally achieved. Super modular design with numerous mounting rings, round as well as square designs with adjustable and fixed options, in various wattages enable nuanced adaptation to different needs. Honey combo filter can be added to provide maximum visual comfort.

FEATURES

LED QUANTITY 1 Led White FINISH

WORKING CURRENT 500mA (20W), 600mA (25W)

RATED POWER 20/25W

RADIANCE ANGLE 15°, 24°, 38°, 55° 50,000 hrs LAMP LIFE MOUNTING Ceiling recessed

CONNECTION Indoor rated connections Ø75 x 102.4mm, 75x75mm **DIMENSIONS**

OPERATION TEMP -20° C - +50° C

On/Off, Phase, 1-10V, Dali CONTROL


ELECTRICAL DATA

POWER CONSUMPTION 20/25W SUPPLY VOLTAGE 220-240V ac

2700K, 3000K, 4000K **COLORS**

80,90 CRI 80lm/W LUMEN

DIMENSIONS



ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	CONTROL	CURRENT	BEAM	1 ANGLE	CRI	FINISH	ACCESSORY	CUSTOM
CMO RS-RF01	20 - 20W	(CT27) 2700K	ND - ON/OFF	500 - 500mA(20W)	15	- 15°	80 - 80	WH - White	HC - Honey Comb	XX
	25 - 25W	(CT30) 3000K	PH - PHASE	600 - 600mA(25W)	24	- 24°	90 - 90		SL - Soft Lens	
		(CT40) 4000K	AN - 1-10V		38	- 38°				
			DA - DALI		55	- 55°				

Sample: CMO RS-RF03 -20 -CT27 - ND - 500 - 15 - 80 - WH - HC - XX











