VERTEX-D48 VTX-D48 Mono





IP67 WATER PROOF

 ϵ

YYZ VETREX D48 series high brightness and easy installation for architectural outdoor solution, used milky diffuse cover and alum end cap, build in DMX512 module and auto-programming. The modular system available in 600mm, 900mm or 1200mm lengths and can be customized as per project's requirement Two installation way can be selected, mounting clip and adjustable brackets. All cables can be hidden into channel, IP67-rated, UV resistant and designed to withstand outdoor element, applicable for various architectural environment.

FEATURES

LED QUANTITY 96 LED(1200MM), 72 LED (900MM), 48 LED (600MM)

FINISH MACHINED ALUMINUM

WORKING VOLTAGE 24/48V DC

RATED POWER 20W (1200MM) /15W (900MM) /10W (600 MM)

BEAM ANGLE 120°

AVAILABLE LENGTH 600MM, 900MM, 1200MM
MOUNTING SURFACE MOUNTING
OPTIC MILKY PC COVER

DIMENSIONS 1200MM(L) x 48MM(W)x 44.6MM(H)

 OPERATION TEMP
 -35° C - +50° C

 STORAGE TEMP
 -20° C - +60° C

 LAMP LIFE
 50000 HRS

BODY COLOR BLACK, LIGHT BLUE, GRAY, GOLD, WHITE, CUSTOM

CONTROL ON/OFF, DALI, DMX


ELECTRICAL DATA


POWER CONSUMPTION 20/15/10W
SUPPLY VOLTAGE 24, 48 DC VOLTS
COLORS 2700K, 3000K, 4000K

CRI 80+

LUMEN 56-95lm/W @ 4000K

DIMENSION







ORDERING LOGIC

PRODUCT	OPTIC		CONTROL	COLOR TEMPERATURE		VOLTAGE	FIXTURE LENGTH		BODY COLOR		CUSTOM
VTX-D48	120 - 120°	ND	- ON/OFF	(CT27)	2700K	24 - 24VDC	600	- 600mm (48 LEDS)	BK	- BLACK	XX
		DA	- DALI	(CT30)	3000K	48 - 48VDC	900	- 900mm (72 LEDS)	LB	- LIGHT BLUE	
		DM	- DMX	(CT40)	4000K		1200	- 1200mm (96 LEDS)	GR	- GRAY	
				(CTXX)	CUSTOM		XX	- CUSTOM	GL	- GOLD	
									WH	- WHITE	
									XX	- CUSTOM	

Sample: VTX-D48 - 120 - ND - CT 27 - 24 - 600 - BK - XX







