WINDOW SILL LIGHT



WSL-Mono



IP66 WATER PROOF ϵ

YYZ Window sill light is with outstanding design, as small as a shell, and the light spot like a pearl inside. It has a high quality LED with longer use life, higher brightness, pure color, circular lens with double light distribution and anti-vertigo design. It is with integrated design of heat dissipating structure, constant current and international AC in and also provides an intelligent adjustment of overall brightness. These surface mounted lighting fixture help in frame shaping since it is with 360° wide illumination range, and are widely used in storefront window, corridors, hallway, tunnel, etc.

A Company of the Comp

FEATURES

MATERIAL Aluminum

FINISH Black, Grey, Custom

RATED POWER 12W
WORKING VOLTAGE 24 Vdc
LED QUANTITY 6nos
BEAM ANGLE 10° x 150°
ROTATION ANGLE 10°

MOUNTING Surface mounted LAMP LIFE 50,000 hrs

DIMENSIONS 320(L)x65(W)x50mm(H)

 OPERATION TEMP
 -40° C - +50° C

 STORAGE TEMP
 -40° C - +80° C

 CONTROL
 On/Off

OPTIC PMMA WEIGHT 0.9kg








ELECTRICAL DATA

POWER CONSUMPTION 12W SUPPLY VOLTAGE 24Vdc

COLORS 2700K, 3000K, 4000K, 5000K, 5700K, 6500K

CRI 80+ LUMEN 720lm

DIMENSION



ORDERING LOGIC

PRODUCT	POWER	OPTIC	COLOR TE	MPERATURE	VOLTAGE	BODY COLOR		CUSTOM	
WSL	12 - 12W	10 x 150 - 10°x150°	(CT27)	2700K	24 - 24VDC	BK	-	BLACK	XX
		XX - CUSTOM	(CT30)	3000K		GR	-	GREY	
			(CT40)	4000K		XX	-	CUSTOM	
			(CT50)	5000K					
			(CT57)	5700K					
			(CT65)	6500K					
			(CTXX)	CUSTOM					

Sample: WSL - 12 - 10x150 - CT 27 - 24 - BK - XX