SYMPHONY ADJUSTABLE DOWNLIGHT



SNY-A



IP40 (€

YYZ Symphony is a type of adjustable recessed LED downlight with quality aluminum body in powder coated, with multiple reflecting angles of anti-dazzle reflector for selection and with excellent heat sink capability. $These \, recessed \, downlights \, with \, symmetrical \, light \, distribution \, to \, achieve \, an \, effective \, task \, or \, ambient \, lighting \, the symmetrical \, light \, distribution \, to \, achieve \, an \, effective \, task \, or \, ambient \, lighting \, the symmetrical \, light \, distribution \, to \, achieve \, an \, effective \, task \, or \, ambient \, lighting \, the symmetrical \, light \, distribution \, to \, achieve \, an \, effective \, task \, or \, ambient \, lighting \, the symmetrical \, light \, distribution \, to \, achieve \, an \, effective \, task \, or \, ambient \, lighting \, the symmetrical \, light \, distribution \, to \, achieve \, an \, effective \, task \, or \, ambient \, lighting \, the symmetrical \, light \, distribution \, to \, achieve \, an \, effective \, task \, or \, ambient \, lighting \, the symmetrical \, light \, distribution \, to \, achieve \, an \, effective \, task \, or \, ambient \, lighting \, the symmetrical \, light \, distribution \, the \, achieve \,$ and are applicable in areas like supermarket, chain stores, shopping malls, villas, hotels, halls.



FEATURES

FINISH White, Black, Silver

WORKING VOLTAGE 100-240V ac

RATED POWER

RADIANCE ANGLE 15°, 24°, 38° 50,000 hrs LAMP LIFE MOUNTING Ceiling recessed

CONNECTION Indoor rated connections Ø90 x 71mm (cutout Ø75mm) **DIMENSIONS**

OPERATION TEMP -30° C - +50° C

CONTROL DALI, 0-10V, Triac, Non-Dimmable

ELECTRICAL DATA


POWER CONSUMPTION 9W


SUPPLY VOLTAGE 100-240V ac

2700K, 3000K, 4000K, 5000K COLORS

CRI LUMEN 90 lm/W

DIMENSIONS











CREE LED Quality





ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE		BEAM ANGLE	FINISH		ACCESSORIES		сиѕтом
SNY-A	9 - 9W	(CT27)	2700K	15 - 15°	WH -	White	FG - I	Frosted Glass	XX
		(CT30)	3000K	24 - 24°	BK -	Black	CG -	Clear Glass	
		(CT40)	4000K	38 - 38°	SL -	Silver			
		(CT50)	5000K						

Sample: SNY-A - 9 - CT27 - 15 - WH - FG - XX