DOME SERIES

DOE-SQ65



IP54 (

 ϵ

YYZ Dome series of architectural downlight features glare free performance with the ultra wide beam angle. Available in variety of sizes to accommodate wattage. Making it versatile for applications with ceiling heights.

FEATURES

MATERIAL Aluminum

FINISH White

RATED POWER 7.5W, 11W

WORKING CURRENT 250mA, 350mA

RADIANCE ANGLE 25°, 60°

MOUNTING Ceiling recessed

CONNECTION Indoor rated connections

LAMP LIFE 50,000 Hrs

DIMENSION 75 x 75x61mm (Cutout 65x65mm)

OPERATIN TEMP -20° C - +50° C CONTROL Non-Dim, 1-10V, Dali









ELECTRICAL DATA


POWER CONSUMPTION 7.5W, 11W SUPPLY VOLTAGE 220-240V AC

COLORS 2700K, 3000K, 4000K

CRI 80, 90

LUMEN 700-750lm @ 7.5W, 900-950lm@ 11W

DIMENSIONS









ORDERING LOGIC

| PRODUCT | WATTAGE | COLOR TEMPERATURE | | BEAM ANGLE | | | FINISH | REFLECTOR FINISH | |
|----------|------------|-------------------|-------|------------|---|-----|-------------|------------------|-------|
| DOE SQ65 | 7.5 - 7.5W | (CT27) | 2700K | 25 | - | 25° | WH - White | MA - | Matt |
| | 11 - 11W | (CT30) | 3000K | 60 | - | 60° | XX - Custom | WH - | White |
| | | (CT40) | 4000K | | | | | BK - | Black |
| | | | | | | | | | |

Sample: DOE SQ65 - 7.5 - CT27 - 25 - WH - MA