

WASH SERIES

WSH 190

Mono IP54 CE

YYZ Wash series downlights are best suited for architectural in addition to general lighting since it enables symmetrical light distribution to get an effective task, accent or general lighting. This series adopt the best technique of heat conduction, and it also features glare free performance with $UGR \leq 19$ even for the ultra wide beam angle.

FEATURES

MATERIAL	Aluminum
FINISH	White, Black
RATED POWER	25W
WORKING VOLTAGE	220-240V AC
RADIANCE ANGLE	38°, 60°
MOUNTING	Ceiling recessed
CONNECTION	Indoor rated connections
LAMP LIFE	50,000 Hrs
DIMENSION	Ø190 x 100mm (Cutout Ø170mm)
OPERATING TEMP	-15° C - +50° C
CONTROL	On/Off, Phase cut dimmable, 0-10V, Dali



BRIDGELUX
LED Quality

240V AC
Working Voltage

25W
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	25W
SUPPLY VOLTAGE	220-240V AC
COLORS	2700K, 3000K, 4000K, 5000K
CRI	80
LUMEN	80 lm/W

ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	BEAM ANGLE	FINISH
WSH190	25 - 25W	(CT27) 2700K	38 - 38°	BK - Black
		(CT30) 3000K	60 - 60°	WH - White
		(CT40) 4000K		XX - Custom
		(CT50) 5000K		

Sample: WSH190 - 25 - CT27 - 38 - BK