

VERTEX FLEX-Y22E-VB/HB RGBW-24V

VTF Y22E



YYZ Vertex flex is designed to provide a very bright, crisp consistent and homogenized illumination that will accentuate any building, structure or artistic flourish. Using 84 high brightness surface mounted LEDs/meter, behind a first class eco-friendly UV-resistant PVC encapsulated flexible chamber material, it helps to provide bright, consistent traces of light in 10 shades of white, single colors of red, green and blue. The fixture consists of uniform and even lighting with no Led hotspot and has a transverse minimum diameter of 30cm. It is easy to be installed, can be cut and re connected with IP68 protected connector. Connectors at both ends offer ease of installation and is supplied in 5m standard rolls-or custom. Operating at 24V, the Vertex Flex features on-board constant-current drive topology, which ensures consistent brightness along the entire run, precise drive current, and long life expectancy. Dimming is achieved with YYZ's dimming compatible power supplies. Two power levels and two control types are also available.



FEATURES

LED QUANTITY	84 Leds / mtr
FINISH	PVC Encapsulated flexible chamber material
WORKING VOLTAGE	24 Volts
RATED POWER	15W/ mtr
RADIANCE ANGLE	160°
LAMP LIFE	50000 hrs
MOUNTING	Mounting clip / Chanel
CONNECTION	Outdoor rated connections
CUTTING INCREMENTS	83.3mm (1 Unit)
DIMENSIONS	17(H) x 16(W)
OPERATION TEMP	-20° C - +50° C
STORAGE TEMP	-20° C - +60° C
WEIGHT	0.325 kg/mtr
CONTINUOUS LENGTH	8mtr

- 84 LEDs / mtr
LED Quality
- 24 VOLTS
Working Voltage
- 15W / mtr
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	15W
SUPPLY VOLTAGE	24 Volts
COLORS	RGBW (W @ 2700K, W@3000K, W@4000K)
CRI	80+
LEDS / 3.3FT	84


ORDERING LOGIC

PRODUCT	BENDING	CONTROL	COLOR TEMPARTURE	VOLTAGE	FIXTURE LENGTH	MOUNTING	CONNECTION	CUSTOM
VTF Y22E	VB - Vertical HB - Horizontal	DMX - DMX CONTROL	(CT RGB+27) RGB + 2700K (CT RGB+30) RGB + 3000K (CT RGB+40) RGB + 4000K	24 (24 VDC)	5 - 5Mtr (####) CUSTOM	CLP - Clip CHL - Chanel	OC - Outdoor Connector	xx


(Order Extrusion and End cap as per site requirement)

Sample: VTF Y22E - VB -DMX - CT RGB+27 - 24 - 5 - CLP - OC - XX


DIMENSION



HORIZONTAL BENDING





VERTICAL BENDING



Note: Unless otherwise stated, the tolerance of the light is $\pm 0.3\text{mm}$.

BENDING DETAILS



The light can only be bent along the light surface. Do not bend smaller than allowed minimum bend diameter.

TYPES OF CONNECTOR


INJECTION-MOULDED CONNECTOR


Note: Unless otherwise stated, the tolerance of the connector is $\pm 0.5\text{mm}$.



INJECTION-MOULDED FRONT CONNECTOR (BOTTOM)



Connects light to power supply with pre-installed bottom feed cable IP67. Available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m lengths.







INJECTION-MOULDED FRONT CONNECTOR (SIDE)

Connects light to power supply with pre-installed side feed cable, IP67. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.





INJECTION-MOULDED FRONT CONNECTOR (END)

Connects light to power supply with pre-installed end feed cable, IP67. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.



INJECTION-MOULDED END CAP


Pre-installed termination protection of the light, IP67.



INJECTION-MOULDED JUMPER

Connects two pieces of lights together with a flexible cable, IP67 Injection-moulded connector. L available in 0.3-1m.


Maximum 8 Jumpers in 20m
Maximum 4 Jumpers in 10m



INJECTION-MOULDED T-FEED


Connects two pieces of lights together with a T joint, energized from middle. IP67 Injection-moulded connector. L1 and L2 available in 0.15-0.5m. L3 available in 0.3-3m.

Maximum 8 T-feeds in 20m
Maximum 4 T-feeds in 10m




DUAL INJECTION-MOULDED CONNECTOR


Note: Unless otherwise stated, the tolerance of the connector is ±0.5mm.



DUAL INJECTION-MOULDED FRONT CONNECTOR (BOTTOM)



Connects light to power supply with pre-installed bottom feed cable, IP68. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.







DUAL INJECTION-MOULDED FRONT CONNECTOR (SIDE)

Connects light to power supply with pre-installed side feed cable, IP68. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.





DUAL INJECTION-MOULDED FRONT CONNECTOR (TOP END)

Connects light to power supply with pre-installed end feed cable, IP68. Cable length available in 0.3m, 1m, 3m, 5m, 10m, 15m, 20m.



DUAL INJECTION-MOULDED END CAP


Pre-installed termination protection of the light, IP68.



DUAL INJECTION-MOULDED JUMPER

Connects two pieces of lights together with a flexible cable. IP68 Dual Injection-moulded connector. L available in 0.3~1m.


Maximum 8 Jumpers in 20m
Maximum 4 Jumpers in 10m



DUAL INJECTION-MOULDED T-FEED


Connects two pieces of lights together with a T joint, energized from middle. IP68 Dual Injection-moulded connector. L1 and L2 available in 0.15~0.5m. L3 available in 0.3-3m.

Maximum 8 T-feeds in 20m
Maximum 4 T-feeds in 10m



ANTI-WICKING FERRULE


Note: Unless otherwise stated, the tolerance is $\pm 0.5\text{mm}$.



ANTI-WICKING FERRULE

The anti-wicking ferrule is located at 115mm ($\pm 5\text{mm}$ tolerance) from the connector on the cable.

For protection against water ingress from inside of cable wire and hence damage the light.




MALE & FEMALE CONNECTOR

Note: Unless otherwise stated, the tolerance is $\pm 2\text{mm}$.





MALE & FEMALE CONNECTOR

For plug and play cable junction, DIY or Pre-installed connector, IP68






MOUNTING PROFILE

STANDARD ALUMINUM PROFILE




DIMENSIONS

Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.




Model	W*H(mm)	Standard Length (mm)	L1 (mm)	L2 (mm)	Screw Hole (mm)	Hole Number	For Product
W22-A/PL	19*18	35	17.5	/	Ø3.5	1	W22
		500	50	200	Ø3.5	3	W22
		1000	100	200	Ø3.5	5	W22
		2000	100	200	Ø3.5	10	W22

PLASTIC PROFILE




Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.









Model	W*H(mm)	Standard Length (mm)	L1 (mm)	L2 (mm)	Screw Hole (mm)	Hole Number	For Product
W22-PC/PL	19*21	500	50	200	Ø3.5	3	W22
		1000	100	200	Ø3.5	5	W22
		2000	100	200	Ø3.5	10	W22

SELF-LOCKING ALUMINUM PROFILE (USING WITH THE CLIP)




Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.




Model	W*H(mm)	Standard Length(mm)	L1(mm)	L2(mm)	L3(mm)	L4(mm)	Hole Screw(mm)	Hole Number	Clip Number
W22-SLA/PL	20.5 x 20	35	17.5	25	5	/	Ø3.5	2	1
		500	50	200	75	350	Ø3.5	3	2
		1000	100	200	150	350	Ø3.5	5	3
		2000	100	200	125	350	Ø3.5	10	6

SELF-LOCKING ALUMINUM PROFILE VER. 2 (USING WITH THE CLIP)




Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.



Model	W*H(mm)	Standard Length(mm)	L1(mm)	L2(mm)	L3(mm)	L4(mm)	Hole Screw(mm)	Hole Number	Clip Number
W22-SLA/PL2	20.7*22.3	35	17.5	/	5	25	Ø3.5	2	1
		500	25	150	50	200	Ø3.5	3	4
		1000	25	190	100	200	Ø3.5	5	6
		2000	25	195	100	200	Ø3.5	10	11

PLASTIC & ALUMINUM COMBINATION PROFILE






Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.

Model	W*H(mm)	Standard Length (mm)	L1 (mm)	L2 (mm)	Screw Hole (mm)	Hole Number	For Product
W22 -PA/PL	20.8*23	35	17.5	/	Ø3.5	1	W22
		500	50	200	Ø3.5	3	W22
		1000	100	200	Ø3.5	5	W22
		2000	100	200	Ø3.5	10	W22

CABLE EXIT ORIENTED ALUMINUM PROFILE

(APPLICABLE TO INJECTION-MOULDED CONNECTOR ONLY)




SELF-LOCKING ALUMINUM PROFILE VER. 2, BOTTOM FEED (USING WITH THE CLIP)



Model: W22-SLA/PL2-B

Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.




SELF-LOCKING ALUMINUM PROFILE VER. 2, MIDDLE FEED (USING WITH THE CLIP)



Model: W22-SLA/PL2-M

Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.


SELF-LOCKING ALUMINUM PROFILE VER. 2, SIDE FEED FROM LEFT (USING WITH THE CLIP)



Model: W22-SLA/PL2-SL



Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.

SELF-LOCKING ALUMINUM PROFILE VER. 2, SIDE FEED FROM RIGHT (USING WITH THE CLIP)



Model: W22-SLA/PL2-SR


Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.



CORNER ALUMINUM PROFILE



(APPLICABLE TO INJECTION-MOULDED CONNECTOR ONLY)

L SHAPE SELF-LOCKING ALUMINUM PROFILE VER. 2 (USING WITH THE CLIP)



Model: W22-SLA/PL2-L

Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.





INWARD L SHAPE SELF-LOCKING ALUMINUM PROFILE VER.2 (USING WITH THE CLIP)




Model: W22-SLA/PL2-IL

Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.





OUTWARD L SHAPE SELF-LOCKING ALUMINUM PROFILE VER.2 (USING WITH THE CLIP)




Model: W22-SLA/PL2-OL

Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.





T SHAPE SELF-LOCKING ALUMINUM PROFILE VER. 2 (USING WITH THE CLIP)



Model: W22-SLA/PL2-T

Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.





X SHAPE SELF-LOCKING ALUMINUM PROFILE VER. 2 (USING WITH THE CLIP)




Model: W22-SLA/PL2-X

Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.



CURVE STAINLESS STEEL PROFILE



Model: W22-CS/PL

Note: Unless otherwise stated, the tolerance of the profile is $\pm 0.5\text{mm}$.

