

ATRIUM 1 SURFACE MOUNT

ATR 1S

IP44 IK06 CE

YYZ Atrium range of modular LED ceiling lights render glare free homogenous light through the use of high quality opal diffuser. Luminaire is provided with suitable mounting brackets required for various types of ceilings. Recommended for wide range of end users from commercial office buildings to high output retail applications.



FEATURES

MATERIAL	CRCA Sheet Steel
FINISH	Epoxy polyester powder coated in white (RAL9016)
RATED POWER	30W, 36W, 40W, 50W, 60W, 75W
WORKING VOLTAGE	220-240V AC
MOUNTING	Surface mounted
CONNECTION	Indoor rated connections
LAMP LIFE	L70 B20 50,000hrs
DIMENSION	595mm x 595mm x 65mm, 1200x300x65mm
OPERATING TEMP	-20° C - +50° C
CONTROL	On/Off, Dali, 1-10V, Emergency Kit

SAMSUNG/LUMILEDS
LED Quality


220-240VAC
Working Voltage

30W/36W/40W/50W/60W/75W
Rated power

ELECTRICAL DATA

POWER CONSUMPTION	30W, 36W, 40W, 50W, 60W, 75W
SUPPLY VOLTAGE	220-240V AC
COLORS	3000K/4000K/6500K
CRI	>80
DELIVERED LUMENS	130lm/W
SDCM	3 SDCM, 2SDCM (On request)

DIMENSIONS



L	W	H
595	595	65
1200	300	65

ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEMPERATURE	INPUT VOLTAGE	FINISH	CONTROL	SIZE - L x W	CUSTOM
ATR 1S	30 - 30W	(CT 30) 3000K	220-240VAC	WH - White	SW - On/Off	A - 595x595 B - 1200x300	XX - XXX
	36 - 36W	(CT 40) 4000K		XX - Custom	DA - Dali		
	40 - 40W	(CT 65) 6500K			AN - 1-10V		
	50 - 50W	(CTXX) CUSTOM			EM - Emergency Kit		
	60 - 60W						
	75 - 75W						

Sample: ATR 1S - 30 - CT30 - 220 - WH - SW - A - XX