AVALANCHE-188 RGBW



AVL 188RGBW

YYZ Avalanche series is a Surface mounted flood luminaire with very low glare rating while reducing light pollution and specially designed for landscapes and in unique structure design shapes. They are made up of die-cast aluminum body and housing covered by anti-corrosion resistant with marine grade stainless steel. It can achieve the desired effect in a wide range of applications and can be applicable in highlighting architectural facades, landscapes, trees, etc

FEATURES

MATERIAL
FINISH
RATED POWER
WORKING VOLTAGE
BEAM ANGLE
MOUNTING
CONNECTION
LAMP LIFE
DIMENSIONS
OPERATION TEMP
STORAGE TEMP
CONTROL

Die-cast aluminum Black /White 30W, 36W, 60W 24V DC, 100~277V AC, 50/60Hz 3°/7°/15°/40°/60° Surface mount Outdoor rated connections 50,000 hrs Ø188 x 130 x 253 mm -30° C - +50° C -20° C - +50° C DMX





ELECTRICAL DATA

POWER CONSUMPTION	
SUPPLY VOLTAGE	
CRI	
COLORS	
LUMEN	

30W, 36W, 60W 100~277V AC, 50/60Hz 85+ RGBW 85-95lm/W

DRAWING







ORDERING LOGIC

PRODUCT	WATTAGE	COLOR TEM	IPERATURE	INPUT VOLTAGE		OPTIC		2	FINISH	CONTROL		ACCESSORIES	
AVL 188RGBW	30 - 30W	(RGBW)	RGBW	DC -	24V DC	3	-	3°	BK - Black	DM -	DMX	HCL - Honey	Louver
	36 - 36W			AC - 10	0~277VAC	7	-	7°	WH - White			CWL -	Cowl
	60 - 60W					15	-	15°					
						40	-	40°					
						60	-	60°					

Sample: AVL 188RGBW - 30 - RGBW - DC - 3 - BK - DM - HCL