# WINDOW SILL LIGHT









The Windowsill Light is an innovative LED luminaire designed for wall and ceiling mounting, featuring a distinctive 3° x 180° blade effect optic. Engineered to accentuate window reveals, it directs LED light from opposing sides through specially developed reflectors, resulting in a uniform arc of light that can illuminate an entire window reveal with a single luminaire. Meticulously crafted, our Windowsill light showcases a sleek, minimalist design that seamlessly harmonizes with any décor. Emitting a gentle, welcoming glow, it turns regular windows into captivating focal points, fostering relaxation and elevating the aesthetic charm of your environment.

# **FEATURES**

MATERIAL Die-cast Aluminum **FINISH** Black, Grey, Custom

RATED POWER 4W, 7W WORKING VOLTAGE 24V DC LED QUANTITY 1No **BEAM ANGLE** 3° x 180° MOUNTING Surface mounted 50,000 hrs LAMP LIFE

Ø 101.20mm x 57.6(H) **DIMENSIONS** 

OPERATION TEMP -20° C - +50° C STORAGE TEMP -40° C - +80° C On/Off, DALI CONTROL

OPTIC PC WEIGHT 0.35kg







# **ELECTRICAL DATA**


POWER CONSUMPTION 4W, 7W SUPPLY VOLTAGE 24V DC


2700K, 3000K, 4000K, 5700K, 6500K **COLORS** 


CRI 80+


LUMEN 4W - 130lm @ 3000°K 7W - 270lm @ 3000°K

## **DIMENSION**









## **ORDERING LOGIC**

WSL Series

PRODUCT	WATTAGE	COLOR TEMPERATURE		OPTIC		VOLTAGE	CONTROL	FINISH	
WSL	4 - 4W	(CT27)	2700K	3 x 180 -	3°x180°	DC - 24V DC	SW - On/Off	GB	- Graphite Black (RAL 9011
	7 - 7W	(CT30)	3000K				DA - DALI	IG	- Iron Grey (RAL7011)
		(CT40)	4000K					SW	- Signal White (RAL 9003)
		(CT57)	5700K					SG	- Signal Green (RAL6032)
		(CT65)	6500K					XX	- Custom Color Finish
		(CTXX)	CUSTOM						

Sample: WSL - 4 - CT27 - 3x180 - DC - SW - GB

